

Wood Preservative

Sikkens Wood Preservative protects wood from the deteriorating effects of micro-organisms like fungi, mold, mildew, bacteria and algae growth. It should be applied as a pretreatment before coating with Sikkens exterior wood finish products for sidings and log homes, or as a temporary coat for decks.

Prevents deterioration of exterior wood from micro-organisms like fungi, mildew, bacteria, algae and rot.

Water repellent.

Compatible as an undercoat for most alkyd finishes, except under the Sikkens Cetol® DEK finishes.

When used with a system, enhances the performance of most Sikkens exterior solvent-borne coatings.

When used alone, does not prevent the natural weathering caused by ultraviolet rays.

Very easy to use.

Exterior use only.

For use in warm humid climates where fungi, mold and/or mildew growth is a problem and in other special circumstances. Use as a pretreatment on exterior wood, such as siding and logs before applying any Sikkens exterior products. Sikkens Wood Preservative should not be applied under any Sikkens Cetol DEK system.

Method - Brush, roller.

Temperature - 50° F. - 95° F.

Thinning - None; ready to use after stirring well.

Coverage (approximate) - 200-400 sq. ft. U.S. gallon, depending on surface porosity and application method. Do not puddle.

Cleaning of equipment - Mineral spirits or equivalent.

Drying Time - Touch dry after 3 hours. Recoatable after 24 hours at 75°F and 65% relative humidity.

CHARACTERISTICS

USE

APPLICATION

Sikkens Wood Preservative must penetrate to work properly. To test for penetration: sprinkle a few drops of water on the wood surface. If the water is absorbed, the surface is ready.

- Do not apply directly over painted or stained surface.
- Do not apply if the moisture content of the wood surface is >21%

Solids by Weight -38.2% ± 2%

Water Repellancy - Exceeds Federal Specification TT-W-572b,3.7 or equivalent.

Active Ingredients - 3 Iodo - 2-Propynyl Butyl Carbamate - 0.5%

Color - Light Amber

V.O.C. - Less than 4.59 lbs./gal., 50 g/L - less water

U.S. gallon, U.S. 5 gallon

Shelf Life - Approximately 5 years in an unopened container.

EPA Reg. No. 5383-92-59016

EPA Est. No. 59016-MI-1

FLASHPOINT:

Approximately 104°F (40°C) (DIN53213)

WARNINGS:

DANGER! RAGS, STEEL WOOL, BRUSHES, ROLLERS AND ANY WASTE WET, SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISPOSED OR STORED. To avoid a spontaneous combustion fire, immediately after each use place rags, steel wool, brushes, rollers or waste in a sealed, water-filled metal container. Keep away from combustible materials. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency. Harmful or fatal if swallowed. Keep out of reach of children. Keep away from open flame or spark. Use only with adequate ventilation. Combustible. Harmful if inhaled, or absorbed through skin. May cause eye and skin irritation. Contains Petroleum Distillate solvents. Keep away from heat and flame. Use only with adequate ventilation. Avoid breathing vapors, mist or substantially saturated atmosphere. Keep containers closed when not in use. Do not take internally. To avoid breathing vapors or mist, open windows and doors or use means to ensure fresh air entry during application and drying. If headaches, dizziness or eyewatering occur, increase fresh air or wear respiratory protection (NIOSH/MSHATC 23° or equivalent) or leave the area.

GENERAL REMARKS

PROPERTIES

PACKAGING

STORAGE

EPA NUMBERS

HEALTH & SAFETY DATA

Close container after each use. Avoid contact with the skin, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before re-use. If swallowed, do not induce vomiting. Call physician immediately. Keep out of reach of children. In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention. DO NOT use, pour, spill, or store near heat or open flame. IN CASE OF FIRE: Use dry chemicals, foam, fog, or CO².

ENVIRONMENTAL HAZARDS:

This pesticide is toxic to fish. Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to the sewer systems without previously notifying the local sewage treatment authority. For guidance, contact your local State Water Board or Regional Office or the EPA.

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings Inc. has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise, the suitability of this product for their purposes. When testing, the complete system that has been chosen must be applied.

**HEALTH & SAFETY
DATA - CONT.****PRODUCT DISCLAIMER**